Material Safety Data Sheet (Prepared according to 29 CFR 1910,1200) Date of Preparation: Revised: 11/11 Prepared By: DD Section - 1 Product and Company Identification **Product Name: Power** Chemical Family: Floor Cleaner Generic Name: Formula: Floor Cleaner, Powder Suppliers Name: Perform Mfg Suppliers Address: 1624 S 45th St Kansas City, KS 66106 Proper Shipping Name: : Non Hazardous Information Phone Number: Emergency Phone No. 913-722-1557 913-722-1557 Personal Protection:B Flammability:0 HMIS Codes Reactivity: 1 Health2 Section - 2 Hazard Ingredients / Identity Information Hazardous Components (Specific Chemical Identity; OSHA PEL | ACGIH/TVL | Other Limits % Wt. Common Name(s)) Sodium Metasilicate 6834-92-0 15ppm 15mg/m³ 10mg/m³ < 29.0 497-19-8 < 60.0 Sodium Carbonate Pine Oil 8002-09-3 < 10.0 Section III - Physical / Chemical characteristics Boiling Point Range °F: N/A Specific Gravity (H₂O =1):2.12 Vapor Pressure (mm Hg.):N/D melting Point: N/A Vapor Density (AIR = 1): N/A Evaporation Rate: N/A Solubility in Water: Miscible (Butyl Acetate = 1) Appearance and Odor: Free Flowing Yellow Powder with Pine Odor % Volatile: N/D pH: Alkaline Section IV - Fire and Explosion Hazard Data Flash Point (Method Used): N/A Flammable limits: LEL UEL N/A N/A Extinguishing Media: Water Fog, CO2, Dry Chemical Special Fire Fighting procedures: SCBA, Protective Clothing Unusual Fire and Explosion Hazards: Extinguish all ignition sources, Flammable Hydrogen Gas may be liberated. Autoignition Temprature: **Section V - Reactivity Data** Stabitity: Unstable Conditions to Avoid: Stable Χ Incompatibility (Materials to avoid): Active Metals, strong acids Hazardous Decomposition or By products: Carbon Monoxide, Carbon Dioxide Hazardous Polymerization: May Occur Will not Occur

Section VI - Health Hazard Information		
Effects of Overexposure:		
Primary Ro	ute of Entry:	<u> </u>
Skin:		Overexposure may produce burns.
Eyes:	Destructive - Exposure may cause burns, eye injury and blindness.	
	Excessive inhalation may damage respiratory tract. Possible nausea, dizziness, and difficulty breathing.	
Ingestion:	Extremely corrosive, large quantities could cause severe pain, nausea, death.	
		First Aid propadures
Skin:	First Aid procedures: Immediately flush skin with plenty of water while removing contaminated clothing. Seek medical attention if irritation persists	
Eyes:	Flush with water for 15 minutes while lifting eyelids to assure complete	
Lycs.	removal. Get medical attention.	
Inhalation:		r. If breathing has stopped, give artificial respiration. Get medical attention.
Ingestion:		ting. If conscious, dilute stomach contents by drinking water. Call a physician immediately.
gco	120 1101 1110000 101111	ang nonototo, and otomas on one by annung nature out a physician influence.
		Section VII - Spills, Leaks and Disposal Procedure
Steps to be	Taken in Case	Material is Released or Spilled:
Otops to be		ate protective and respiratory equipment.
Prevent spills from entering sewers or any unauthorized water systems.		
Waste Disp	osal Method:	
Dispose in accordance with appropriate Federal, State and Local regulations.		
		•
		Section VIII - Exposure Controls / Personal Protection
Respiratory Protection:		NIOSH/OSHA approved respirators for materials in
		section 2 when ventilation is restricted. Use in well ventilated area
Protective Gloves		None required.
Other Protective Equipment:		nt: None required.
Ventilation		Sufficient ventilation in volume and pattern should be provided to
		keep air contamination at a minimum.
Eye Protection:		Safety glasses or goggles.
		Section IX - Special Precautions and Comments
Handling Pre	ecautions:	Keep out of reach of children.
		For Trained Industrial and Institutional Personnel Only.
Storage Rec	uirements:	Keep container tightly closed when not in use
0	In	house of the board of the sector of
Comments: Practice good hygine after handling this material.		